

Silicon (Si)

Diameter tolerance $\pm 0.0004''$ (± 0.01 mm)

Thickness tolerance $\pm 0.002''$ (± 0.05 mm)

Surface Quality 60/40

CAT#	DIA, in	DIA, mm	CT, in	CT, mm
SI-HS-2	0.08	2.0	0.04	1.0
SI-HS-3	0.12	3.0	0.06	1.5
SI-HS-4	0.16	4.0	0.08	2.0
SI-HS-5	0.20	5.0	0.10	2.5
SI-HS-6	0.24	6.0	0.12	3.0
SI-HS-8	0.32	8.0	0.16	4.0
SI-HS-10	0.39	10.0	0.20	5.0
SI-HS-12	0.47	12.0	0.24	6.0
SI-HS-14	0.55	14.0	0.28	7.0
SI-HS-18	0.71	18.0	0.36	9.0
SI-HS-20	0.79	20.0	0.40	10.0
SI-HS-25	1.00	25.4	0.50	12.7

Zinc Selenide CVD Grade (ZnSe)

Diameter tolerance $\pm 0.0004''$ (± 0.01 mm)

Thickness tolerance $\pm 0.002''$ (± 0.05 mm)

Surface Quality 60/40

CAT#	DIA, in	DIA, mm	CT, in	CT, mm
ZC-HS-2	0.08	2.0	0.04	1.0
ZC-HS-3	0.12	3.0	0.06	1.5
ZC-HS-4	0.16	4.0	0.08	2.0
ZC-HS-5	0.20	5.0	0.10	2.5
ZC-HS-6	0.24	6.0	0.12	3.0
ZC-HS-8	0.32	8.0	0.16	4.0
ZC-HS-10	0.39	10.0	0.20	5.0
ZC-HS-12	0.47	12.0	0.24	6.0
ZC-HS-14	0.55	14.0	0.28	7.0
ZC-HS-18	0.71	18.0	0.36	9.0
ZC-HS-20	0.79	20.0	0.40	10.0
ZC-HS-25	1.00	25.4	0.50	12.7

Custom sizes and specifications are available