

# Potassium Bromide (KBr)

Dia tolerance  $+0,-0.005''$  ( $+0,-0.13\text{mm}$ )  
Th tolerance  $\pm 0.005''$  ( $\pm 0.13\text{mm}$ )  
Clear Aperture 85%

Parallelism 3 arc min  
Flatness 1/10 wave at 10.6  $\mu\text{m}$   
Surface Finish 60/40

CAT#	DIA, in	DIA, mm	TH, in	TH, mm
KB-W-12-2	0.5	12.7	0.079	2.0
KB-W-12-3	0.5	12.7	0.118	3.0
KB-W-25-3	1.0	25.4	0.118	3.0
KB-W-25-4	1.0	25.4	0.157	4.0
KB-W-25-5	1.0	25.4	0.197	5.0
KB-W-38-4	1.5	38.1	0.157	4.0
KB-W-38-6	1.5	38.1	0.236	6.0
KB-W-50-6	2.0	50.8	0.236	6.0
KB-W-50-8	2.0	50.8	0.315	8.0
KB-W-63-6	2.5	63.5	0.236	6.0
KB-W-63-8	2.5	63.5	0.315	8.0
KB-W-76-8	3.0	76.2	0.315	8.0
KB-W-76-10	3.0	76.2	0.394	10.0

# Potassium Chloride (KCl)

Dia tolerance  $+0,-0.005''$  ( $+0,-0.13\text{mm}$ )  
Th tolerance  $\pm 0.005''$  ( $\pm 0.13\text{mm}$ )  
Clear Aperture 85%

Parallelism 3 arc min  
Flatness 1/10 wave at 10.6  $\mu\text{m}$   
Surface Finish 60/40

CAT #	DIA, in	DIA, mm	TH, in	TH, mm
KC-W-12-2	0.5	12.7	0.079	2.0
KC-W-12-3	0.5	12.7	0.118	3.0
KC-W-25-3	1.0	25.4	0.118	3.0
KC-W-25-4	1.0	25.4	0.157	4.0
KC-W-25-5	1.0	25.4	0.197	5.0
KC-W-38-4	1.5	38.1	0.157	4.0
KC-W-38-6	1.5	38.1	0.236	6.0
KC-W-50-6	2.0	50.8	0.236	6.0
KC-W-50-8	2.0	50.8	0.315	8.0
KC-W-63-6	2.5	63.5	0.236	6.0
KC-W-63-8	2.5	63.5	0.315	8.0
KC-W-76-8	3.0	76.2	0.315	8.0
KC-W-76-10	3.0	76.2	0.394	10.0

Custom sizes and specifications are available